

**RECEIVED  
CENTRAL FAX CENTER****JUN 26 2008****PATENT  
P57003****IN THE CLAIMS**

Pursuant to 37 CFR §121(c), the claim listing, including the text of the claims, will serve to replace all prior versions of the claims, in the application.

Please cancel claims 3 and 9 without prejudice or disclaimer of their subject matter, and amend claims 1, 4, 7 and 10 as follows:

1. (Currently Amended) A method of configuring a direction-based Core Based Tree (CBT) for a CBT-based overlay multicast, the method comprising:

requesting and receiving information on child nodes pre-subscribed to a core node at an arbitrary terminal node to be subscribed to the CBT;

calculating a direction between the terminal node and each of the child nodes and transmitting information on the child node having a minimum resultant value to the core node along with a subscription request message; and

comparing the calculated direction between a corresponding child node and the terminal node with the calculated direction between child nodes pre-subscribed to the core node at the core node and subscribing the terminal node to either the child node or a parent node of the corresponding child node in accordance with the comparison to configure the CBT;

wherein calculating the direction comprises using internal and external angles and a height of a triangle having respective distances between the core node and two arbitrary nodes adjacent to the core as respective sides of the triangle.

2. (Original) The method according to claim 1, further comprising periodically transmitting and receiving a hello packet at the core node and the terminal node to and from the parent node, the child node and a brother node to confirm a state of the corresponding node and reconfiguring the configured CBT in response to the confirmed

PATENT  
P57003

5 state of the corresponding node.

Claim 3. (Canceled)

1 4. (Currently Amended) The method according to claim [[3]] 1, wherein  
2 calculating the direction comprises using the formula:

3  $\text{direction} = (\alpha + \beta) * y$

4 wherein the triangle has nodes a1, C0 and a2, C0 being a core node, and a1 and a2  
5 being arbitrary nodes, C0 and a2 forming a bottom side of the triangle, " $\alpha$ " being an  
6 internal angle formed by a side C0a1 and a side C0a2 of the triangle; " $\beta$ " being an  
7 external angle formed by the side C0a1 and a side a1a2 of the triangle, "y" being a height  
8 of the triangle, and "direction" being the calculated direction.

1 5. (Original) The method according to claim 1, wherein calculating the direction  
2 further comprises determining that the child node having a minimum resultant value and  
3 the terminal node have a same forwarding direction of packets from the core node, the  
4 terminal node being determined to be either a child node or a parent node of the  
5 corresponding child node

1 6. (Original) The method according to claim 1, wherein:  
2 when the resultant value of calculating the direction between the corresponding  
3 child node and the terminal node is smaller than the resultant value of calculating the  
4 direction between the pre-subscribed child nodes at the core node, the terminal node is  
5 subscribed to the child node of the core node and a message is transmitted to the pre-  
6 subscribed child node to re-subscribe to the child node of the terminal node; and

PATENT  
P57003

7 the pre-subscribed child node withdraws from the core node and subscribes to the  
8 child node of the terminal node in response to the message.

1 7. (Currently Amended) A program storage device, readable by a machine,  
2 tangibly embodying a program of instructions executable by the machine to perform a  
3 method of configuring a direction-based Core Based Tree (CBT) for a CBT-based overlay  
4 multicast, the method comprising:

5 requesting and receiving information on child nodes pre-subscribed to a core node  
6 at an arbitrary terminal node to be subscribed to the CBT;

7 calculating a direction between the terminal node and each of the child nodes and  
8 transmitting information on the child node having a minimum resultant value to the core  
9 node along with a subscription request message; and

10 comparing the calculated direction between a corresponding child node and the  
11 terminal node with the calculated direction between child nodes pre-subscribed to the  
12 core node at the core node and subscribing the terminal node to either the child node or a  
13 parent node of the corresponding child node in accordance with the comparison to  
14 configure the CBT;

15 wherein calculating the direction comprises using internal and external angles and  
16 a height of a triangle having respective distances between the core node and two arbitrary  
17 nodes adjacent to the core as respective sides of the triangle.

1 8. (Original) The program storage device according to claim 7, the method further  
2 comprising periodically transmitting and receiving a hello packet at the core node and the  
3 terminal node to and from the parent node, the child node and a brother node to confirm a  
4 state of the corresponding node and reconfiguring the configured CBT in response to the  
5 confirmed state of the corresponding node.

PATENT  
P57003

## Claim 9. (Canceled)

1           10. (Currently Amended) The program storage device according to claim [[9]] 7,  
2 wherein calculating the direction comprises using the formula:

3           
$$\text{direction} = (\alpha + \beta) * y$$

4           wherein the triangle has nodes a1, C0 and a2, C0 being a core node, and a1 and a2  
5 being arbitrary nodes, C0 and a2 forming a bottom side of the triangle, " $\alpha$ " being an  
6 internal angle formed by a side C0a1 and a side C0a2 of the triangle; " $\beta$ " being an  
7 external angle formed by the side C0a1 and a side a1a2 of the triangle, "y" being a height  
8 of the triangle, and "direction" being the calculated direction.

1           11. (Original) The program storage device according to claim 7, wherein  
2 calculating the direction further comprises determining that the child node having a  
3 minimum resultant value and the terminal node have a same forwarding direction of  
4 packets from the core node, the terminal node being determined to be either a child node  
5 or a parent node of the corresponding child node.

1           12. (Original) The program storage device according to claim 7, wherein:  
2           when the resultant value of calculating the direction between the corresponding  
3 child node and the terminal node is smaller than the resultant value of calculating the  
4 direction between the pre-subscribed child nodes at the core node, the terminal node is  
5 subscribed to the child node of the core node and a message is transmitted to the pre-  
6 subscribed child node to re-subscribe to the child node of the terminal node; and  
7           the pre-subscribed child node withdraw from the core node and subscribes to the  
8 child node of the terminal node in response to the message.